

RECEIVED
CENTRAL FAX CENTER

NOV 30 2006

AMENDMENTS TO THE CLAIMS:

Replace the claims with the following rewritten listing:

1. - 51. (Cancelled)

52. (New) Apparatus for monitoring muscle activity so as to detect a particular said muscle activity and to distinguish the occurrence of said particular muscle activity from the occurrence of at least one other muscle activity, said apparatus comprising

- means for providing signals indicative of muscle activity, for example EMG signals,

- means for processing of said signals in order to detect said particular activity,

and

- means for providing a feedback signal,

wherein said device is operable in a set-up mode and in a use mode,

and wherein, in said set up mode, said device is user controllable to receive as a first reference input signals from said means for providing signals which are indicative of a said other muscle activity and to receive as a second reference input signals from said means for providing signals which are indicative of said particular muscle activity,

and wherein said device is configured in said setup mode to process said first reference signals and said second reference signals to identify therefrom at least one distinguishing criterion which differentiates said first reference input signals from said second reference input signals,

and wherein in said use mode said device is configured to provide said feedback signal in response to detecting in the provided signals said at least one distinguishing criterion identified in the set up mode.

53. (New) Apparatus according to claim 52, wherein said device is configured in said setup mode to process said first reference signals and said second reference signals to identify therefrom (as said distinguishing criterion) at least one frequency in said signals, the amplitude of said signals at which frequency differentiates said first reference input signals from said second reference input signals,

and wherein in said use mode said device is configured to provide said feedback signal in response to detecting in the provided signals at least a predetermined amplitude at said at least one frequency identified in the set up mode.

54. (New) Apparatus according to claim 52, wherein, in said set up mode, said device is user controllable to receive as said second reference input signals from said means for providing signals which are indicative of an essentially maximal muscle activity, for example a maximal jaw clenching activity.

55. (New) Apparatus according to claim 52, wherein, in said set up mode, said device is user controllable to receive as said first reference input signals from said means for providing signals which are indicative of a said other muscle activity which is a normally occurring muscle activities, such as producing one or more grimaces.

56. (New) Apparatus according to claim 52, wherein said apparatus comprises means for registering and storing said signals indicative of muscle activity during a time interval.

57. (New) Apparatus according to claim 52, wherein said apparatus is adaptable by having means for adjusting the intensity of said feedback signal.

58. (New) Apparatus according to claim 52, wherein said means for processing of said signals in order to detect a particular activity comprises means for pattern recognition.

59. (New) Apparatus according to claim 52, wherein said means for providing signals indicative of muscle activity comprises one or more electrodes for sensing of EMG-signals.

60. (New) Apparatus according to claim 52, wherein said means for providing signals indicative of muscle activity comprises one or more electrodes for sensing of EEG-signals.

61. (New) Apparatus according to claim 60, wherein said device comprises means for testing said electrodes and in particular the connectivity to the user by supplying a test voltage or test current to the electrode (s), measuring the resulting current or required voltage and comparing the result with reference value(s).

62. (New) Apparatus according to claim 52, wherein said means for providing signals indicative of muscle activity comprises a microphone, a sensor for sensing of vibrations and/or other sensor means.

63. (New) Apparatus according to claim 52, wherein said apparatus comprises means for storing data corresponding to measured and/or processed signals.

64. (New) Apparatus according to claim 63, wherein the apparatus further comprises a computer and means for transferring stored data thereto.

65. (New) Apparatus according to claim 52, wherein said apparatus comprises a user module for wearing on the head, e. g. on the forehead, on or in the ear.

66. (New) Apparatus according to claim 52, wherein said apparatus comprises a slave module and a master module, said slave module being designed for wearing by a human being.

67. (New) Apparatus according to claim 52, wherein said apparatus comprises display means for displaying instructions and/or results stemming from a monitoring session.

68. (New) A method for monitoring muscle activity so as to detect a particular said muscle activity and to distinguish the occurrence of said particular muscle activity from the occurrence of at least one other muscle activity, said method comprising

- receiving signals indicative of muscle activity, for example EMG signals,
- processing said signals in order to detect said particular activity, and
- providing a feedback signal,

wherein said device is operated in a set-up mode and in a use mode,
and wherein, in said set up mode, said device is user controlled to receive as a first reference input signals from said means for providing signals which are indicative of a said other muscle activity and to receive as a second reference input signals from said means for providing signals which are indicative of said particular muscle activity,
and wherein said device is configured in said setup mode to process said first reference signals and said second reference signals to identify therefrom at least one distinguishing criterion which differentiates said first reference input signals from said second reference input signals,
and wherein in said use mode said device is configured to provide said feedback signal in response to detecting in the provided signals said at least one distinguishing criterion identified in the set up mode.